





Product data card

Pladur® Relief Textured Wood coating

 34-700 Rabka-Zdrój
ul. Kilińskiego 49a

 T: +48 18 26 85 200
F: +48 18 26 85 215

 biuro@blachotrapez.eu
www.blachotrapez.eu

 NIP 676-243-17-30
REGON 121387287

Pladur® Relief Textured Wood

General Information



Painted sheets with metallic layer ZM EcoProtect®. PLADUR ZM coating system consists in coating the steel core with a layer of zinc and magnesium weighing 130 g/m² and at least two layers (primer and top layer) of organic coating.

Advantages and properties

Sheets with a proprietary surface structure imitating wood, 3-layer coating system, coating thickness min. 36 microns.



Pladur® Relief Textured Wood



Material

The type and mass of the metallic coating on both sides together	ZM 130 [g/m ²]
Coating system	3-layer
Organic coat thickness side A	Min 36 [µm]
Environment classification according to EN ISO 12944-2	C4
Reaction to fire	A2
Resistance to considered to external fire	B roof (t1), B roof (t2), B roof (t3)

Guarantee

Perforation guarantee for the environmental classification C1-C3	55 years
Perforation guarantee for environmental classification C4	35 years
Guarantee for lacquer delamination	20 years